

## CapStart®

### FEATURES

#### GENERAL

- Capacitor can be re-charged 500,000 times, providing many years of service and can be recharged in under one minute
- Powercells are non gassing, non leaking, and maintenance free
- Operating temperature range: -49° F to +122° F
- Activation switch with 30 ft. cord
- Extra large pneumatic tires for rough terrain
- Powercells are charged by the built-in 120 volt AC fully automatic charger
- Includes full-power jaw clamps with 10 ft. of 4/0 cable
- Quick-disconnect red plug for plug-to-plug operation
- Includes reverse polarity and dead short circuitry protection
- Extreme heavy duty case
- Available as a 12 volt model
- Extra large pneumatic tires for easy mobility
- Dimensions: 48"H x 20"W x 26"D
- Shipping weight: 190 lbs. (approx.)

#### GENERAL

- Capacitor can be re-charged 500,000 times, providing many years of service and can be recharged in under one minute
- Powercells are non gassing, non leaking, and maintenance free
- Operating temperature range: -49° F to +122° F
- Activation switch with 30 ft. cord
- Powercells are charged by the vehicle's electrical system or by the built-in 120 volt AC fully automatic charger
- Includes full-power jaw clamps with 26 ft. of 4/0 cable
- Quick-disconnect red plug for plug-to-plug operation
- Includes reverse polarity and dead short circuitry protection
- Available as a 12 volt model
- Dimensions: 14"H x 44"W x 20"D
- Shipping weight: 250 lbs. (approx.)

### Portable CapStart®

**13-085-10 12 Volt**



### Vehicle-Mounted CapStart®

**13-095-10 12 Volt**



Distributed by:

**Cantec** Systems

(613) 725-3704

<http://www.cantecsystems.com>